





SNAP-IN TERMINATION OPTIONS



M61



VS21,VS31



VS41,VS51



\* PC Mounting for M61,VS21,VS31,VS41,VS51 refer to M6,VS2,VS3,VS4,VS5 respectively.

CONTACT MATERIAL OPTIONS

Coding	Contact Material	Terminal Plating	Rating	Agency Approvals
Q	Silver <sup>1</sup>	Silver plated <sup>1</sup>	5Amps @ 125VAC or 28VDC 2Amps @ 250VAC	
P		Tin plated <sup>5,7</sup>		
R	Gold <sup>2</sup>	Gold plated <sup>4</sup>	0.4VA max @ 20V max (AC or DC)	
K		Tin plated <sup>5,6</sup>		
G	Silver <sup>1</sup>	Gold over <sup>3</sup> silver	5Amps @ 125VAC or 28VDC 2Amps @ 250VAC	

1. Movable Contact / Terminals: Copper alloy, silver plated.
2. Movable Contact: Copper alloy with gold plated over nickel plated.
3. Terminals: Silver plated with outer layer in gold plating.
4. Terminals: Copper alloy, with gold plated over nickel plated.
5. Outer Terminals: Copper alloy with pure tin plated.
6. Terminal Contact: Gold plated over nickel plated.
7. Terminal Contact: Palladium nickel alloy (or Silver) plated.

\* P, K not available with M1 and M3 terminals.

\* 6Amps (Movable Contact: coin silver, silver plated) available to model ON-NONE-ON only and no agency approval when ordered.