









Digital Multi-Meter Test Lead and Accessory

	<p>Model: UT-C07 Description: Standard 2mm Tip Modular Rating: 10A Insulator: PolyProplene</p>				
	<p>Model: <table border="1" data-bbox="1024 890 1360 957"> <tr> <td>UT-C08</td> <td>UT-C08A</td> </tr> <tr> <td>M4 Thread</td> <td>UNC 8-32 Thread</td> </tr> </table> Description: Standard 2mm Tip Rating: 10A Insulator: PolyProplene</p>	UT-C08	UT-C08A	M4 Thread	UNC 8-32 Thread
UT-C08	UT-C08A				
M4 Thread	UNC 8-32 Thread				
	<p>Model: <table border="1" data-bbox="1024 1268 1360 1335"> <tr> <td>UT-C09</td> <td>UT-C09A</td> </tr> <tr> <td>M4 Thread</td> <td>UNC 8-32 Thread</td> </tr> </table> Description: Sharp Stainless Tip Modular Rating: 10A Insulator: PolyProplene</p>	UT-C09	UT-C09A	M4 Thread	UNC 8-32 Thread
UT-C09	UT-C09A				
M4 Thread	UNC 8-32 Thread				
	<p>Model: UT-C10 Description: Standard 4mm Tip Modular Rating: 10A Insulator: PolyProplene</p>				

Digital Multi-Meter Test Lead and Accessory

 <p>UL, CE</p>	<p>Model: UT-2696AA Description: 4mm Test Lead Rating: 10A 1000V CATIII Wire Type: Silicon UL3430 0.75mm² (175/0.08mm)</p>
 <p>UL, CE</p>	<p>Model: UT-2696AB Description: 4mm Test Lead Rating: 10A 1000V CATIII Wire Type: Silicon UL3430 0.75mm² (175/0.08mm)</p>
	<p>Model: UT-D01 Description: Medium Crocodile Clip to Banana Plug Patch Cord Wire Type: Silicon UL3430 0.75mm² (175/0.08mm) Insulator: PVC, Polypropylene</p>
	<p>Model: UT-D02 Description: Medium Crocodile Clip to Banana Plug Patch Cord Wire Type: Silicon UL3430 0.75mm² (175/0.08mm) Insulator: PVC, Polypropylene</p>

Digital Multi-Meter Test Lead and Accessory



Description: Medium Alligator Clip
 Rating: 5A
 Insulator: PVC

Model:

UT-B02	UT-B02A	UT-B03	UT-B04
M4 Thread for UT-2660BA/BB UT-2660AA/AB	UNC 8-32 Thread for UT-2660BA/BB UT-2660AA/AB	for UT-2660CA	for UT-2660DA



Model: UT-B05
 Description: Large Alligator Clip
 Opening size 35mm
 Rating: 35A

Digital Multi-Meter Test Lead and Accessory



Model:UT-A03
Oscilloscope Probes
high quality general purpose oscilloscope probe
two 4mm Stackable Banana plug
one BNC connector
Low Contact Resistance
Good insulation performance with full sheath



Model:UT-A04
Oscilloscope Probes
high quality general purpose oscilloscope probe
two 4mm Stackable Banana plug
one BNC connector
Low Contact Resistance
Good insulation performance



Model:UT-A01
Low Cost Kelvin Clip Lead Set
Two 0.94m(37in) long probes with alligator style clips, each with opposing blade source and sense connections to color coded standard safety banana plugs.
Design for applications requiring Kelvin connection to wires, axial leaded components, and other terminals able to be clipped onto. The miniature blade design accommodates narrow available width applications as well as general lighter duty applications.
The maximum jaw opening is 9.14mm (0.36in) and the blade width is 2.92mm (0.115in)
For use with Picotest M3500A, M3510A



Model:UT-A02
Low cost, Single Pin, Kelving Probes
Two 1.55m long, single fixed pin probes with source and sense leads per probe and color coded standard safety banana plugs.
Designed for applications requiring Kelvin resistance measurements with the convenience of a single point of circuit contact. The kelvin connection at the base of each probe pin results in very low resistance errors, eliminating all wire and probe body resistance.
sold by Picotest exclusively