











Multi-Colour

	Part No.	Emitted Colour	Lens Colour	λ D (nm)	Electro-Optical Characteristics (IF= 20mA)				Viewing Angle (deg)	Common Anode / Cathode
					Vf (V)		Iv (mcd)			
					Typ.	Max.	Min.	Typ.		
	B5-4RGB-CBA	Red	Water Clear	625	2.0	2.4	840	1200	20	Common Anode
		Green		525	3.2	3.8	2590	3700		
		Blue		470	3.2	3.8	490	700		
	B5-4RGB-CBC	Red	Water Clear	625	2.0	2.4	840	1200	20	Common Cathode
		Green		525	3.2	3.8	2590	3700		
		Blue		470	3.2	3.8	490	700		
	B5-3RGB-CBA	Red	White Diffused	625	2.0	2.4	420	600	45	Common Anode
		Green		525	3.2	3.8	700	1000		
		Blue		470	3.2	3.8	140	200		
	B5-3RGB-CBC	Red	White Diffused	625	2.0	2.4	420	600	45	Common Cathode
		Green		525	3.2	3.8	700	1000		
		Blue		470	3.2	3.8	140	200		
	B5-30EG	Red	White Diffused	633	2.1	2.6	5	10	50	Common Cathode
		Green		570	2.1	2.6	5	10		
	B5-30EG-CA	Red	White Diffused	633	2.1	2.6	5	10	50	Common Anode
		Green		570	2.1	2.6	5	10		
	B5-40SYLOR-85A	Yellow	Water Clear	592	2.0	2.4	-	7200	25	Common Anode
		Red		625	2.0	2.4	-	7200		
	B5-40SBLOR-C	Blue	Water Clear	470	3.2	3.8	-	1300	25	Common Cathode
		Red		625	2.0	2.4	-	1800		

	B5-40EGLOR-85A	Green	Water Clear	525	3.2	3.8	-	10000	25	Common Anode
		Red		625	2.0	2.4	-	10000		
	B5-31GSR	Green	White Diffused	570	2.1	2.6	-	6	50	-
		Red		645	1.9	2.4	-	25		