

SPECIFICATION

MATERIAL

Insulator: ABS + PC

Shell : Stainless

ELECTRICAL

Operation voltage: 5.0 V

Current rating: 0.9 Amps max.

Contact resistance: 80 m ohms initial

Insulation resistance: 1000 M ohms min @ 500 VDC

Dielectric withstanding voltage: 500 VAC / minute

Temperature range: -0°C TO +60°C

Part no.

G A 03 A D C0 XX A XX
1 2 3 4 5 6 7 8 9

1.SERIES NO.

G=Finished

2.A=Adapter

3.03=USB C Plug To MicroBF 3.0

4.A=TYPE A

5.GREEN OPTION:

D=RoHS2(Matte)

(Halogn-Free)

6.CUSTOMER NO:

C0=COXOC type

7.Technology Code:

00=RD 5.1k Ohm






01=RP 10k Ohm

8.A=TRAY

9.COLOR:

W0=WHITE

B0=BLACK



UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±2°
0.	±0.50
.0	±0.30
.00	±0.20



CHANT SINCERE CO.,LTD
TEL:886-02-8647251 FAX:886-02-8647292

SCALE:	AS SHOWN	UNIT:	mm
DRAWN	PEARL	DATE	12/03/2015
CHECKED	<i>范志斌</i>	DATE	12/03/15
APPROVED	<i>范志斌</i>	DATE	12/03/15

DRAWN NAME:	(PDR-15047)
PRODUCT NO.	GA03ADC0XXAXX
FILE NAME:	C-GA03ADC0XXAXX(GB)

REV.	DESCRIPTION	DATE
A	ECN-1512005(Som) X2 Change to A	12/03/2015